



TWMNF

N-type Half-cell
Bifacial Module(66)

66HD700-720W


High Power Output
Low LCOE



Maximum Power
720W+



TIER 1
Bloomberg
NEW ENERGY FINANCE



Utility-scale
PV Plants



12
YEAR
Materials
Warranty




30
YEAR
Power
Warranty

www.tongwei.com.cn



Learn More

DRAWINGS (Unit: mm)



Electrical Characteristics (STC)

Moduel type: TWMNF-66HDXXX

Maximum Power: Pmax [W]	700	705	710	715	720
Open Circuit Voltage: Voc [V]	48.60	48.77	48.94	49.11	49.28
Short Circuit Current: Isc [A]	18.35	18.40	18.45	18.50	18.55
Voltage at Maximum Power: Vmp [V]	40.35	40.52	40.69	40.86	41.03
Current at Maximum Power: Imp [A]	17.35	17.40	17.45	17.50	17.55
Module Efficiency: η [%]	22.5	22.7	22.9	23.0	23.2

* STC: Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5

Electrical Characteristics (NMOT)

Maximum Power: Pmax [W]	526	530	534	538	541
Open Circuit Voltage: Voc [V]	46.17	46.33	46.49	46.65	46.82
Short Circuit Current: Isc [A]	14.82	14.86	14.90	14.94	14.98
Voltage at Maximum Power: Vmp [V]	37.55	37.73	37.90	38.08	38.18
Current at Maximum Power: Imp [A]	14.01	14.05	14.09	14.13	14.17

* NMOT: Irradiance 800W/m², Ambient Temperature 20°C, AM=1.5, Wind Speed 1m/s

ELECTRICAL CHARACTERISTICS (Rear Power Gain)

5%	Maximum Power: Pmax[W]	735	740	745	750	756
	Module Efficiency: η [%]	23.7	23.8	24.0	24.1	24.3
15%	Maximum Power: Pmax[W]	805	810	816	822	828
	Module Efficiency: η [%]	25.9	26.1	26.3	26.5	26.7
25%	Maximum Power: Pmax[W]	875	881	887	893	900
	Module Efficiency: η [%]	28.2	28.4	28.6	28.7	29.0

TEMPERATURE PARAMETERS

Temperature Coefficient (Pmax)	-0.28%/°C
Temperature Coefficient (Voc)	-0.24%/°C
Temperature Coefficient (Isc)	+0.046%/°C
NMOT	45±2°C


MAXIMUM RATINGS

Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	35A
Power Output Tolerance	0~+3%
Bifaciality	80±5%


MECHANICAL PARAMETERS

Cells	TNC(N Type Monocrystalline Cell)
Cell Orientation	132[6×22]
Dimension	2384±2×1303±2×33mm
Weight	37.9kg
Front Glass	2.0mm AR coated heat strengthened glass
Rear Glass	2.0mm heat strengthened glass
Frame	Anodized aluminum alloy frame
Junction Box	IP68, 3 diodes
Output Cable	4.0mm ²
Cable Length	+400mm, -200mm or ±1400mm,length can be customized
Wind/Snow Load	2400Pa/5400Pa
Packaging	33pcs per pallet, 594pcs per 40'HC

WARRANTY



I-V CURVE



CERTIFICATIONS

Quality Management System and Product Certification

ISO 9001: 2015/Quality management system
ISO 14001: 2015/Environmental management system
ISO 45001: 2018/Occupation health safety management system
ISO 50001: 2018/Energy management system
IEC 62941: 2019/Quality system for PV module manufacturing
IEC 61215/61730, IEC 62804(PID), IEC 61701(Salt),
IEC 62716 (Ammonia), IEC 60068-2-68(Sand)



Email: sales@tongwei.com Website: en.tongwei.com.cn Add: No.588, Middle Section Tianfu Avenue, High-Tech Zone, Chengdu, China (Sichuan) Pilot Free Trade Zone Tel: +86 0286066455

Statement: With technological process and product update, there maybe deviation between the technical parameters of Tongwei's module products and the technical parameters contained in the specification, and Tongwei Solar has the right to adjust the technical parameters at any time without notifying the customer, the final interpretation of the technical specification is vested in Tongwei Solar. (Preview-20240703)